



Technical Specifications – Prior™ Tiles				
		Prior™ 11C	Prior™ 16	Prior™ 16C
Tile:	Material	100% PVC – UV resistant		
	Construction	Closed	Open	Closed
	Thickness	11 mm	16 mm	16 mm
	Size	Nominal 200x200 mm – useable 195x195 mm when installed		
	Colour	Graphite		
	Mass	5420 gms/m ²	7110 gms/m ²	9340 gms/m ²
Finished Tiles:	Flammability	Tested according to BS 4790 Low radius of effect of ignition		
	Fire retardant version	Tested according to EN ISO 13501: rated Class C _{FL} –s2		N/A
	Wear Resistance	Tested according to Vetterman Drum Test		
		22,000 cycles	66,000 cycles	66,000 cycles
	Friction resistance	N/A	Tested according to DS/EN ISO 8295 (2004) – Class B	N/A
	Ozone Resistance	50 pph ozone at 30°C		
	Temperature resistance	- 30° C to +50° C		
	Packing:	60 tiles per box (Approx. 2.28 sqm)		
	Pallet loading:	60 boxes per pallet	40 boxes per pallet	40 boxes per pallet

All specifications are subject to change to meet the ongoing improvements of our products.

NB: Prior™ FR modular tiles are in black colour