



**PRIOR 11C HD** Modular grid system for entrance flooring solutions

<b>Product description</b>	UV resistant modular grid		
	<b>Wear resistance</b>	Heavy (for both foot and wheeled traffic)	
	<b>Total thickness</b>	Approx. 11 mm	
	<b>Total Weight</b>	Approx. 7150 gr/m <sup>2</sup> (+/- 2%)	
<b>Grid Construction</b>	<b>Structure</b>	Closed construction	
	<b>Composition</b>	100% recyclable and UV resistant PVC	
	<b>Temperature resistance</b>	From -30°C up to +50°C (suitable for outdoor use)	
	<b>Mass</b>	Approx. 7150 gr/m <sup>2</sup>	
	<b>Grid thickness</b>	Approx. 11 mm	
<b>Performance Testing</b>	<b>Fire Classification</b>	Cfl-s1	(EN ISO 13501)
	<b>Wear Resistance</b>	Heavy Pass at 22,000 cycles	(Vettermann Drum test)
<b>Individual grid size</b>	<b>Nominal</b>	210 x 210 mm (approx.)	
	<b>Usable when installed</b>	200 x 200 mm (approx.)	
<b>Installation</b>	PRIOR 11C HD is fully compatible with TERGO 11C HD and FORMA 11C HD		
<b>ADA / BS 8300 / ISO 21542 Compliant</b>	Yes		
<b>LEED® Point Contributor</b>	Yes		
<b>ISO Manufacturing Certification</b>	ISO 9001		
<b>ISO Environmental Certification</b>	ISO 14001		
<b>Origin</b>	UK		
<b>Warranty</b>	Please refer to our OBEX 5 year wear warranty		

Please Note: As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/ labelling /processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility/liability. Each customer must test and be responsible for its own specific use, further processing, labelling, marketing, etc. All sales are exclusively subject to our standard terms of sales posted at [www.milliken.com/terms](http://www.milliken.com/terms) (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing.