

PRIOR 16C HD Modular grid system for entrance flooring solutions

Product description	UV resistant modular grid		
	Wear resistance	Severe (for both foot and wheeled traffic)	
	Total thickness	Approx. 16 mm	
	Total Weight	Approx. 9475 gr/m ² (+/- 2%)	
Grid Construction	Structure	Closed construction	
	Composition	100% recyclable and UV resistant PVC	
	Temperature resistance	From -30 °C up to +50 °C (suitable for outdoor use)	
	Mass	Approx. 9475 gr/m ²	
	Grid thickness	Approx. 16 mm	
Performance Testing	Fire Classification	Cfl-s1	(EN ISO 13501)
	Wear Resistance	Severe Pass at 66,000 cycles	(Vettermann Drum test)
Individual grid size	Nominal	210 x 210 mm (approx.)	
	Usable when installed	200 x 200 mm (approx.)	
Installation	PRIOR 16C HD is fully compatible with TERGO 16C HD and FORMA 16C HD		
ADA / BS 8300 / ISO 21542 Compliant	Yes		
LEED® Point Contributor	Yes		
ISO Manufacturing Certification	ISO 9001		
ISO Environmental Certification	ISO 14001		
Origin	UK		
Warranty	Please refer to our OBEX 5 year wear warranty		

Please Note: As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/ labelling /processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility/liability. Each customer must test and be responsible for its own specific use, further processing, labelling, marketing, etc. All sales are exclusively subject to our standard terms of sales posted at www.milliken.com/terms (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing.