

Boulevard™ 6000

Boulevard 6000 is constructed from 100% solution dyed nylon yarn and incorporates a heavy scraper fibre for optimum dirt removal and moisture retention. The range is available in a choice of eight colours in either sheet or tile format.

Boulevard 6000 can be used in conjunction with a primary entrance mat and in some situations can be used as stand-alone matting in entrances and access points.

The range is designed to complement Esplanade 6000 and Access 6000 primary barrier matting.

Typical applications: Used in conjunction with a primary mat or as a stand-alone mat. Also in lift lobbies, corridors and service areas.

Product Information

See secondary matting product selection guide - **pages 36-37**



Warranties:	Tile	Sheet
Wear	10 Years	10 Years

Specification:	Tile	Sheet
Product Dimensions	500mm x 500mm	25m x 2m
Product Construction	Tufted Cut Pile	
Surface Yarn	100% Aquafil Alto Chroma SDN	
Total Carpet Weight	4750 g/m ²	4750 g/m ²
Tufted Pile Weight	950 g/m ²	950 g/m ²
Primary Backing	Non-woven	Non-woven
Secondary Backing	Bitumen	pvc
Total Carpet Thickness	9mm	8mm
Pile Height	5mm	5mm

Performance Specification	
Classification BSEN 1307	Class 3
Static Electricity ISO 6356	<2kV
Thermal Resistance BS 4745: 1990	1.3 (TOG)

Flammability	
BSEN 13501-1	Class Cfl-s1

For recommended adhesives contact Technical Services on 01625 428922.



Environmental Profiles
Cert No. ENP 399

BRE Global (BREEAM):
For specific ratings visit: www.greenbooklive.com

Samples

An accurate colour match can only be achieved by requesting the relevant product sample(s) from Gradus Technical Support on 01625 428922.

500mm x 500mm View



Indigo



Shadow
LRV 5.36



Walnut
LRV 2.86



Rosemary
LRV 4.45



Galaxy
LRV 2.56



Indigo
LRV 4.01



Atlantic
LRV 1.90



Nickel
LRV 3.70



Nightfall
LRV 1.48